International Journal of AI, Big Data, Computational and Management Studies
Noble Scholar Research Group | Volume 7, Issue 2, PP 398-408, 2026
ISSN: 3050-9416 | https://doi.org/10.63282/3050-9416.IJAIBDCMS-V7I2P151

Original Article

AI-Driven Intelligent Document Processing for Insurance and Prior Authorization: OCR-Based Data Extraction, Enterprise Validation, and Automated Downstream Processing

Srikanth Reddy Gudi
Cigna Evernorth Health Services Inc., Charlotte, North Carolina, USA.

Received On: 02/05/2026 ***Revised On: 31/05/2026*** ***Accepted On: 08/06/2026*** ***Published On: 15/06/2026***

Abstract: *Insurance and healthcare prior-authorization operations continue to receive clinically and administratively relevant information through heterogeneous documents, including scanned forms, physician notes, referral packets, diagnostic attachments, and payer correspondence. Optical character recognition (OCR) can convert pixels into text, but reliable automation requires a broader mechanism that determines document type, extracts semantically typed entities, normalizes values, verifies them against enterprise records and domain constraints, and controls downstream actions under uncertainty. This paper presents a reference architecture for AI-driven intelligent document processing (IDP) that separates perceptual confidence from operational validity. The proposed pipeline combines document classification, OCR or visual-document understanding, entity extraction, terminology normalization, multilayer validation, risk-aware routing, and idempotent downstream orchestration. A formal decision model is defined in which each extracted entity is evaluated by recognition confidence, field criticality, syntactic validity, cross-field consistency, and enterprise-reference agreement before it can trigger an automated action. Because no proprietary insurance corpus or production measurements were supplied for this study, the paper deliberately avoids invented performance results. Instead, the framework is evaluated through requirements traceability to FHIR-based prior-authorization standards, failure-mode analysis, scenario walkthroughs, and a reproducible empirical protocol specifying OCR, extraction, validation, automation, latency, and safety metrics. The resulting design provides a technically testable path from document recognition to controlled enterprise automation while preserving human review for ambiguous or high-risk cases.*

Keywords: *Intelligent Document Processing, Optical Character Recognition, Document AI, Prior Authorization, Insurance Automation, Enterprise Validation, FHIR, Human-In-The-Loop, Workflow Orchestration, Healthcare Interoperability.*

1. Introduction

Insurance and healthcare administrative workflows are document intensive even when the surrounding enterprise is digitally mature. Prior-authorization requests can include physician orders, clinical notes, referral forms, treatment plans, and laboratory reports, imaging reports, coverage documents, and supporting correspondence. The information required for a payer decision may therefore be distributed across machine-generated PDFs, portal exports, scanned paper, faxes, or images. The operational problem is not simply that the documents are unstructured; it is that the same concept may be represented differently across documents and must ultimately be reconciled with member, provider, benefit, authorization, and clinical records. The persistence of manual prior-authorization work is well documented. The American Medical Association has reported a substantial physician and staff burden associated with prior authorization, while the Centers for Medicare & Medicaid Services (CMS) has pursued API-based interoperability requirements intended to reduce administrative friction [16], [19].

OCR is a necessary technology for many scanned-document workflows, but OCR alone does not solve the enterprise problem. A string can be recognized correctly and still be unusable because its semantic type is wrong, its format is invalid, its context is inconsistent, or the corresponding enterprise record does not exist. Modern document-AI research has progressively addressed this limitation by combining textual, spatial, and visual information. LayoutLM and its successors jointly model text and page layout [5]-[7]; DocFormer integrates text, vision, and spatial features [10]; FormNet and BROS emphasize structural and two-dimensional relationships [11], [12]; LiLT addresses language-independent layout representations [13]; and UDOP unifies vision, text, and layout for multiple document-processing tasks [14]. OCR itself has also moved toward transformer-based recognition, as illustrated by

TrOCR [8], while Donut demonstrates an OCR-free document-understanding alternative that avoids OCR error propagation in some settings [9].

These advances improve the perceptual and semantic layers of document understanding, yet an insurance or prior-authorization platform must additionally answer an operational question: when is an extracted value sufficiently trustworthy to trigger an enterprise action? This question becomes critical for identifiers, diagnosis and procedure codes, dates, coverage fields, provider data, and authorization attributes because an automated error may propagate into claims, utilization-management, clinical-administrative, or member-facing systems. Healthcare interoperability standards reinforce this requirement. FHIR defines a common resource model for exchanging healthcare information [17], and the HL7 Da Vinci Prior Authorization Support (PAS) implementation guide specifies FHIR-based structures and workflows for prior-authorization exchange [18]. Thus, document processing must eventually produce data that are not merely readable but conformant, contextually coherent, traceable, and safe to consume.

The engineering context further complicates the problem. AI components are embedded in distributed software systems whose reliability depends on service contracts, dependency management, observability, idempotency, retries, and resource behavior. Production-focused work has emphasized the operational impact of memory leaks, dependency conflicts, concurrency problems, and performance degradation in enterprise Java systems [1]. More broadly, machine-learning systems accumulate hidden technical debt through data dependencies, feedback loops, configuration complexity, and undeclared consumers [22], while software-engineering studies of ML systems show that reliable deployment requires practices beyond model training [23]. In regulated settings, assurance must span the machine-learning lifecycle rather than only the predictive component [24].

This paper therefore treats intelligent document processing as a controlled enterprise decision pipeline. The central contribution is an architecture in which recognition confidence is necessary but not sufficient for automated commitment. Extracted fields pass through syntactic, semantic, contextual, and enterprise-reference validation before a risk-aware policy decides whether to auto-accept, request further validation, send to manual review, or reject. The framework incorporates provenance and audit logging, data minimization, secure handling of electronic protected health information (ePHI), and failure isolation. It is intentionally compatible with OCR-based and OCR-free document-understanding models so that organizations can select the most appropriate perceptual technology without changing the validation and orchestration contract.

The paper makes four contributions. First, it formalizes the distinction between textual correctness and operational validity. Second, it defines an end-to-end IDP architecture for insurance and prior authorization with explicit validation and routing stages. Third, it derives safety and reliability properties that can be tested independently of a specific OCR or transformer model. Fourth, it specifies a reproducible empirical evaluation protocol without inventing data or results. The latter is important because no proprietary production corpus, labeled authorization dataset, or measured runtime log was provided for this study; accordingly, all new numerical performance claims are intentionally omitted.

2. Related Work and Technical Context

2.1. OCR and Visual Document Understanding

Classical OCR systems separate page analysis, character recognition, and language post-processing. Transformer-based recognition reduces some of these hand-engineered boundaries. TrOCR, for example, uses pretrained image and text transformers for end-to-end text recognition and demonstrates the value of transfer learning across printed, handwritten, and scene text [8]. Nevertheless, downstream enterprise tasks rarely operate on characters alone. They require relations among labels, values, tables, sections, and document regions.

Layout-aware pretraining addresses this requirement. LayoutLM jointly models text and layout and showed that spatial information materially improves form understanding and other document tasks [5]. LayoutLMv2 adds image features and multimodal alignment objectives [6], while LayoutLMv3 unifies text and image masking within a general-purpose Document AI architecture [7]. DocFormer similarly combines text, vision, and spatial features through multimodal attention [10]. FormNet and BROS demonstrate that structural modeling and two-dimensional spatial relations can improve key-information extraction, particularly when conventional token serialization loses layout semantics [11], [12]. LiLT extends structured document understanding across languages by decoupling layout learning from language-specific text encoders [13]. UDOP further treats heterogeneous document tasks through a unified vision-text-layout model [14].

OCR-free approaches provide an alternative. Donut maps document images directly to structured outputs and was motivated partly by the computational cost and error propagation associated with external OCR pipelines [9]. An enterprise architecture should therefore avoid coupling validation logic to a single recognition strategy. Whether text is produced by OCR, multimodal token classification, sequence generation, or a hybrid system, the downstream contract should express typed entities, confidence or uncertainty information where available, provenance, and spatial evidence.

2.2. Datasets and Evaluation Practice

Public datasets such as FUNSD provide annotated noisy scanned forms for text detection, OCR, entity labeling, and relation extraction [15]. Such datasets are valuable for benchmarking document understanding, but they do not reproduce the complete operational environment of prior authorization. Real workflows contain organization-specific forms, mixed-quality attachments, clinical terminology,

payer-specific requirements, member and provider lookups, and downstream state transitions. Consequently, high entity-level F1 on a public dataset cannot by itself establish safe automation.

This distinction parallels evaluation lessons from other machine-learning domains. Gunda compared multiple classifiers for software defect prediction using multiple performance measures rather than a single score [2], and further compared Random Forest, Logistic Regression, and K-Nearest Neighbors across accuracy, precision, recall, F1, and ROC-oriented measures [3]. Although software-fault prediction is a different task, the methodological principle transfers: a system should be evaluated according to the operational consequences of different error types. For IDP, character error rate, field exact match, entity F1, and false auto-accept rate, manual-review rate, and downstream transaction correctness measure different failure surfaces and should not be collapsed into one metric.

2.3. Healthcare and Prior-Authorization Interoperability

FHIR R4 provides a resource-oriented standard for healthcare information exchange [17]. The Da Vinci PAS implementation guide builds on FHIR and defines structures and operations for electronic prior-authorization workflows, including interactions between requesting systems and payer systems [18]. CMS has also finalized interoperability and prior-authorization requirements for impacted payers, including a Prior Authorization API that supports documentation requirements and request/response exchange [16]. These standards are central to downstream processing because an IDP system should not terminate at extracted JSON; it should map validated content into governed enterprise and interoperability representations.

Healthcare document automation must also operate within privacy and security constraints. The HIPAA Security Rule requires administrative, physical, and technical safeguards for ePHI, including access control, audit controls, integrity protection, authentication, and transmission security [20]. The proposed architecture therefore treats security and auditability as cross-cutting system properties, not optional post-processing features.

2.4. Enterprise Reliability and Responsible AI

Enterprise AI reliability is affected by both software and model lifecycle concerns. Bandari discusses production challenges such as memory leaks, dependency conflicts, and performance degradation in Java enterprise systems [1]. Sculley et al. identify hidden technical debt specific to machine-learning systems [22], while Amershi et al. describe software-engineering challenges observed across industrial ML development [23]. Ashmore et al. argue that assurance evidence must be generated throughout the ML lifecycle [24]. NIST AI RMF 1.0 similarly frames AI risk management around governance, mapping, measurement, and management activities [21]. These perspectives motivate explicit controls for model versioning, monitoring, fallback behavior, provenance, and human oversight.

Domain-adjacent studies also illustrate the broader movement from raw AI predictions toward integrated applications. Krishna et al. combine deep visual learning with an application-level human-computer interaction objective [4], while Gudi describes an OCR- and microservices-oriented framework for digitizing fax-based prescription workflows [25]. The present work differs by making enterprise validation and risk-controlled downstream commitment the primary architectural boundary.

3. Problem Formulation and Design Objectives

3.1. Document and Entity Model

Let an incoming document package be represented by D = {I, T, L, M}, where I is the image or rendered page content, T is recognized or generated text, L is the spatial/layout representation, and M is document metadata such as source channel, timestamp, sender context, and file attributes. A document-understanding component produces a set of candidate entities E = {e1, e2, en}. Each candidate entity is represented as:

$$e_i = (v_i, \tau_i, c_i, p_i, q_i) \quad (1)$$

Where v_i is the extracted value, τ_i is the predicted semantic type, c_i is model confidence or an uncertainty proxy, p_i identifies page/spatial provenance, and q_i captures extraction metadata such as model version and evidence span. The representation is deliberately model agnostic: an OCR-plus-NER pipeline and an OCR-free generative model can emit the same enterprise contract.

The critical distinction is between recognition correctness and operational acceptability. Define X_i as the event that the textual or semantic extraction is correct and O_i as the event that the value is operationally acceptable for downstream use. In general:

$$P(O_i \mid c_i) \neq P(X_i \mid c_i) \quad (2)$$

Because operational acceptability depends on constraints that are not visible to the recognizer. A member identifier may be read perfectly but fail an eligibility lookup; a procedure code may be valid but inconsistent with a diagnosis or date; a provider identifier may be syntactically correct but inactive for the request context. Therefore, c_i cannot be used as the sole automation gate.

3.2. Validation State

For each entity, the framework computes four validation components. S_i denotes syntactic validity, including length, checksum, type, and regular-expression constraints. T_i denotes semantic or terminology validity, such as membership in an allowed code system. C_i denotes contextual consistency across fields and documents, including temporal and relational rules. X_i denotes external or enterprise-reference agreement, obtained through governed lookups to systems of record. The validation vector is:

$$V_i = [S_i, T_i, C_i, X_i] \quad (3)$$

Each component can be binary, categorical, or probabilistic depending on the use case. For example, an

unavailable reference service should not be interpreted as a failed lookup; it should be represented as an indeterminate technical state. This separation prevents infrastructure errors from being misclassified as business invalidity.

3.3. Risk-Aware Routing

Let k_i represent field criticality and let h_i summarize document-level quality or anomaly indicators. The routing policy selects a disposition R (e_i) from {auto-accept, validate/hold, manual-review, reject/request-information}:

$$R(e_i) = f(c_i, k_i, V_i, h_i, \pi) \quad (4)$$

Where π denotes enterprise policy. A practical implementation should use stricter thresholds for high-impact fields than for low-risk metadata. The policy can be deterministic, probabilistic, or learned, but the final decision must be explainable in terms of observable evidence and policy state. The architecture therefore separates model inference from policy commitment.

3.4. Design Objectives

Table 1: Design Objectives for Enterprise IDP

Objective	Property	Operational interpretation
O1	Contain uncertainty	No low-confidence or validation-failed critical field directly commits a downstream action.
O2	Preserve traceability	Every output is linked to source page/region, model version, validation events, and final disposition.
O3	Support interoperability	Validated entities can be mapped to enterprise schemas and FHIR/PAS resources.
O4	Be recoverable	Technical failures are retryable without duplicating business actions.
O5	Protect ePHI	Access, encryption, audit, and data-minimization controls span ingestion through retention.
O6	Remain model agnostic	OCR-based, layout-aware, and OCR-free recognizers can share the same validation contract.

4. Proposed Ai-Driven IDP Architecture

Fig. 1 summarizes the proposed pipeline. The stages are intentionally separated by typed contracts so that model upgrades, enterprise integrations, and policy changes can be tested independently. Provenance, security, observability, and idempotency are cross-cutting concerns rather than isolated services.




Fig 1: End-To-End Intelligent Document Processing Pipeline

4.1. Secure Ingestion and Document Assembly

Ingestion accepts files from portals, APIs, batch interfaces, fax gateways, object stores, or other approved channels. The service assigns an immutable document identifier, validates file type and size, performs malware scanning where applicable, records source metadata, and computes a content hash. Multi-page packets are assembled deterministically so that subsequent retries operate on the same logical package. Raw documents are stored only in approved encrypted repositories with role-based access and retention controls consistent with enterprise policy and HIPAA safeguards [20].

Duplicate suppression should occur before expensive inference. A combination of source identifier, content hash, and business key can detect exact or near-duplicate submissions. Importantly, duplicate detection must not delete evidence; it should link equivalent submissions to a single processing lineage while retaining audit history.

4.2. Document Classification and Page Segmentation

A prior-authorization packet may mix request forms, clinical notes, laboratory reports, imaging results, letters, and unrelated pages. A document classifier therefore operates before field extraction. The classifier can use text, visual, and layout features from models such as LayoutLM-family architectures [5]-[7], DocFormer [10], or UDOP [14]. Page-level predictions are aggregated into document-level segments so that extraction models receive context-appropriate inputs.

Classification confidence is itself a routing signal. A low-confidence page should not be silently forced into the nearest class because an incorrect class can activate the wrong schema and create systematic extraction errors. The framework permits an “unknown/other” class and routes ambiguous documents to a generic extractor or review queue.

4.3. OCR or Visual-Document Understanding

For scanned documents, OCR produces tokens, bounding boxes, confidence values, and page coordinates. TrOCR is one example of a transformer-based recognizer [8]. Layout-aware models then combine the recognized text with geometry and image evidence. Where suitable, OCR-free models such as Donut can directly produce structured outputs [9]. The architecture does not assume one of these strategies is universally superior; instead, it requires that the chosen recognizer return evidence sufficient for downstream provenance and quality analysis.

Image-quality preprocessing may include orientation correction, deskewing, contrast normalization, de-noising, and page-cropping. However, preprocessing must be versioned because aggressive transformations can alter clinical or administrative evidence. The original image remains the source of record for review and audit.

4.4. Entity Extraction and Structured Representation

Entity extraction identifies business-relevant fields such as member identifiers, patient names, dates of birth, provider identifiers, service dates, diagnosis codes, procedure codes, and requested service descriptions, place of service, urgency indicators, and authorization-related fields. Depending on document type, extraction may use token classification, key-value linking, sequence generation, table parsing, or rules combined with ML. Structural models such as FormNet and BROS are particularly relevant to form-like inputs because they model neighborhood and spatial relationships [11], [12].

Each extracted entity is emitted with value, semantic type, source coordinates, confidence, extraction model version, and optional alternatives. No field is yet considered enterprise valid at this stage. That design prevents an extraction service from assuming authority over business truth.

4.5. Normalization and Terminology Mapping

Normalization converts equivalent surface forms into canonical representations. Dates are mapped to an enterprise date format; identifiers are stripped of formatting characters under explicit rules; names are normalized without destroying original evidence; and clinical or administrative codes are mapped only when the mapping source is governed. Free-text service descriptions may be retained alongside coded values rather than overwritten.

The normalizer must distinguish deterministic transformation from semantic inference. Removing punctuation from a known identifier format is deterministic; inferring an ICD code from narrative text is a model-based transformation and therefore requires its own confidence, provenance, and validation path.

4.6. Multilayer Enterprise Validation

The proposed validation stack is shown in Fig. 2. Validation proceeds from low-cost local checks to higher-cost enterprise queries. This order reduces unnecessary external calls while preserving a clear failure explanation.




Fig 2: Four-Layer Validation Stack Preceding Automated Commitment

Layer 1 performs syntactic validation: required-field presence, data type, allowed character set, length, checksum, and format rules. Layer 2 performs semantic validation against governed dictionaries, terminology services, code sets, and document-specific schemas. Layer 3 evaluates cross-field and temporal consistency, such as whether dates occur in a permissible order or whether requested-service attributes are compatible with the document type. Layer 4 reconciles the data with enterprise systems of record, including member, provider, coverage, authorization, and reference services.

Validation services should return structured outcomes rather than Boolean values. Recommended statuses include Valid, Invalid, Not Found, Conflict, Not Applicable, Technical Failure, and Indeterminate. This taxonomy is important because a temporary enterprise outage must not be treated as evidence that the extracted field is wrong.

4.7. Risk-Aware Decision and Human Review

The routing service combines model uncertainty, field criticality, validation state, and workflow policy. Fig. 3 illustrates the decision boundary. High-confidence, low-risk fields that satisfy all required validation constraints can be

auto-accepted. High-confidence fields with unresolved enterprise validation are held rather than committed. Low-confidence or conflicting high-risk fields are presented to reviewers with the original page region, candidate value, alternatives, and validation explanation.




Fig 3: Risk-Aware Routing From Extracted Entity to Operational Disposition

Human review is therefore not a generic "fallback screen." It is an evidence-based exception path. Reviewer corrections are recorded separately from model outputs so that they can support error analysis and, after governance approval, future retraining. Direct online learning from reviewer edits is not assumed because unreviewed feedback loops can introduce drift and technical debt [22].

4.8. Downstream Processing and Idempotent Orchestration

After validation and routing, accepted entities are assembled into a canonical request model and mapped to the destination contract. In a FHIR-based implementation, this layer may construct resources and operations aligned with the Da Vinci PAS guide [18]. The orchestrator then performs downstream actions such as case creation, attachment indexing, request submission, status update, or work-queue assignment. Each action uses an idempotency key derived from the document package and business operation so that retries cannot create duplicate authorizations or duplicate workflow tasks.

Infrastructure retries are separated from business retries. A network timeout can be retried automatically under bounded policy. A payer response requesting additional information creates a new business state rather than a blind retry. This separation is essential for safe automation.

4.9. Observability, Provenance, and Governance

Every processing stage emits structured events containing correlation identifiers, timestamps, model and rule versions, decision codes, latency, and error categories. Sensitive values should not be copied into general-purpose logs; tokenization, masking, or secure audit stores are preferred. Model-monitoring dashboards should separate input-quality drift, extraction drift, validation mismatch rates, reviewer correction rates, and downstream failure rates.

AI governance follows the principle that risk management spans the lifecycle. The NIST AI RMF functions of govern, map, measure, and manage provide a useful organizational frame [21]. Model replacement, threshold adjustment, terminology updates, and rule changes should therefore be version-controlled and subject to test evidence appropriate to the risk of the affected workflow.

5. Formal Safety and Reliability Properties

5.1. No-Invalidated-Commit Property

For a critical entity e_i, define Req (V_i) as the set of validation predicates required by policy. Let Commit (e_i) indicate that the value is used in a downstream side-effecting action. The primary safety invariant is:

$$Commit\ (e_i) \Rightarrow \forall v \in Req\ (V_i),\ v = PASS \quad (5)$$

This invariant prevents OCR confidence from bypassing enterprise controls. If a required validator is unavailable, the predicate does not equal PASS and the commit is blocked or routed to a governed exception policy.

5.2. Provenance Completeness

For every committed value, the system must retain a chain from destination field to normalized value, extracted candidate, source coordinates, source document, and model/rule versions. If Prov (e_i) denotes that complete chain, then:

$$Commit\ (e_i) \Rightarrow Prov\ (e_i) = complete \quad (6)$$

The property supports audit, reviewer explanation, incident reconstruction, and model regression analysis. Provenance is especially important when multiple documents contain conflicting values.

5.3. Idempotent Side Effects

Let A (k, x) be a downstream action executed with idempotency key k and payload x. For duplicate delivery of the same logical operation:

$$A\ (k, x) \circ A\ (k, x) = A\ (k, x) \quad (7)$$

This property can be implemented through destination-side idempotency support, an orchestration ledger, or transactional outbox patterns. It reduces the risk that retries caused by network or dependency failures generate duplicate cases or submissions.

5.4. Uncertainty Containment

For each field type τ, policy defines an auto-accept threshold $\theta\tau$ and a criticality-adjusted validation requirement. If $c_i < \theta\tau$, automatic commitment is disallowed regardless of downstream availability. For high-impact fields, policy may also require agreement between two evidence channels, such as extraction plus enterprise lookup. This creates a conservative boundary in which uncertainty increases review rather than increasing silent error.

6. Evaluation Methodology

A credible evaluation of the proposed system requires a labeled document corpus and production-like integration environment. Because neither was supplied to this study, this section defines a reproducible protocol instead of reporting invented results. Researchers or practitioners can execute the protocol on de-identified or synthetic documents that reflect their document mix and then report the metrics below.

6.1. Dataset Construction and Splitting

The evaluation corpus should stratify document type, source channel, and image quality, number of pages, handwritten content, table presence, language, and known difficult cases. At minimum, the annotation should identify document class, target entities, entity spans or bounding boxes, normalized values, and enterprise-validation ground truth. Public form datasets such as FUNSD [15] can be used for component benchmarking, but domain-specific prior-authorization documents are necessary for end-to-end conclusions.

Data should be split at the document-package or case level so that pages from the same authorization do not appear in both training and test sets. If templates repeat frequently, template-aware splitting should be used to measure generalization to unseen layouts. A temporal holdout is recommended when documents or payer rules change over time.

6.2. Baselines

Table 2: Recommended Baselines for Empirical Evaluation

ID	Baseline	Purpose
B0	Manual processing	Human extraction and entry; used for workflow-time and error comparison where measured.
B1	OCR + fixed templates	OCR followed by coordinates/regex; no learned layout model.
B2	OCR + layout-aware model	OCR plus LayoutLM/DocFormer/FormNet-family extractor.
B3	OCR-free VDU	Direct image-to-structure model such as Donut where appropriate.
B4	Proposed full pipeline	Best extraction baseline + multilayer enterprise validation + risk-aware routing.

6.3. Extraction Metrics

OCR should be measured with character error rate (CER) and word error rate (WER) on a representative subset. Structured extraction should report exact match for high-impact fields and micro/macro precision, recall, and F1 for entity types. Table and key-value extraction should additionally report relation accuracy when downstream semantics depend on links between labels and values. The use of multiple metrics is consistent with broader machine-learning evaluation practice [2], [3].

Confidence calibration should also be assessed because the architecture uses confidence in routing. Expected calibration error or reliability diagrams can determine whether a nominal confidence corresponds to observed correctness. Poorly calibrated scores should be transformed or replaced by empirically validated uncertainty estimates before policy thresholds are set.

6.4. Validation and Safety Metrics

The most important enterprise metric is the false auto-accept rate (FAAR): the proportion of automatically committed critical fields that are incorrect or operationally invalid. This differs from extraction accuracy because it measures error after validation and routing.

$$FAAR = N(\text{wrong auto-commits}) / N(\text{all auto-commits}) \quad (8)$$

Other required metrics include validation precision/recall, enterprise lookup mismatch rate, manual-review rate (MRR), straight-through processing rate (STP), reviewer correction rate, and unresolved/indeterminate rate. A useful comparison is to hold FAAR below a predefined safety bound and then compare STP among routing policies. This avoids optimizing automation volume at the expense of hidden error.

6.5. Performance and Reliability Metrics

Latency should be reported at the component and end-to-end levels using median, p95, and p99 values. Throughput should be measured in pages or document packages per unit time at defined concurrency. Resource metrics include CPU, memory, GPU utilization where applicable, queue depth, and external-call volume. Production concerns such as memory behavior and dependency failures are relevant because a high-accuracy model that destabilizes the hosting system is not operationally acceptable [1].

Resilience testing should inject dependency timeouts, transient network failures, malformed documents, duplicate deliveries, and partial downstream failures. The primary reliability measures are retry success rate, duplicate-side-effect count, mean time to recovery for transient incidents, and percentage of failed cases that retain complete provenance.

6.6. Statistical Analysis

For paired document-level comparisons, bootstrap confidence intervals can be used for F1, exact match, FAAR,

and STP differences. McNemar-type tests can compare paired correctness outcomes where assumptions hold. Latency distributions should be compared with nonparametric summaries because service latency is typically skewed. Reported improvements should include confidence intervals and absolute differences, not only relative percentages. No such values are claimed in this paper because the required test corpus and measured runtime observations were not supplied.

7. Analytical Validation and Scenario-Based Results

This section evaluates the architecture logically against representative failure conditions. The "result" is the expected system behavior implied by the formal policy and component contracts; it is not a claim of measured production performance. This form of analysis is appropriate for establishing whether the design can contain known failure classes before an empirical deployment study is executed.

Table 3: Scenario-Based Analytical Validation

Scenario	Condition	Expected disposition	Validated property
S1	Clean typed form; high-confidence extraction; all validations pass	Auto-accept and construct downstream request	Normal straight-through path.
S2	Low-quality scan; critical identifier confidence below threshold	Manual review; no commit	Uncertainty containment.
S3	Identifier recognized with high confidence but member lookup conflicts	Block auto-commit; show lookup conflict	Separates recognition from operational validity.
S4	All fields valid but downstream API times out	Retry with same idempotency key	Prevents duplicate side effects.
S5	Two documents provide conflicting service dates	Hold case; contextual conflict presented to reviewer	Cross-document consistency control.
S6	Terminology service unavailable	Mark technical failure; do not classify code invalid	Failure-domain separation.
S7	Unknown document type mixed into packet	Route page to generic/unknown path	Avoids forced misclassification.

Scenario S1 verifies the normal-path composition of extraction, validation, and orchestration. The significance is not that a high-confidence output is accepted; it is that acceptance occurs only after all policy-required validation states are PASS. Scenario S2 verifies that low recognition confidence on a critical field increases review rather than silently reducing data quality. Scenario S3 is the central enterprise case: an OCR engine can be correct at the character level while the business value is still invalid. Because enterprise validation is independent of recognition confidence, the architecture blocks the transaction and preserves both pieces of evidence.

Scenarios S4 and S6 test technical failure isolation. A timeout during a downstream write is not a document error and is handled through retry using an idempotency key. By contrast, an unavailable terminology service leaves semantic validation indeterminate rather than invalid. This prevents operational outages from contaminating model-quality metrics or triggering inappropriate denial logic. S5 tests contextual consistency when two otherwise plausible values conflict. The architecture does not guess which date is correct; it escalates the evidence for review. S7 protects against schema poisoning caused by forced document classification.

The scenario analysis also demonstrates why a monolithic "AI confidence" score is insufficient. The same extraction confidence can lead to different operational outcomes depending on field criticality, validation state, document context, and downstream availability. This supports the paper's core claim that enterprise automation must treat recognition and commitment as separate control planes.

8. FHIR/Pas Integration and Enterprise Mapping

The proposed canonical model is intended to bridge unstructured evidence and structured prior-authorization exchange. FHIR provides a standardized representation for healthcare information [17], while the Da Vinci PAS implementation guide defines profiles and operations relevant to prior-authorization requests and responses [18]. The mapping layer should therefore operate only on validated canonical entities. For example, patient/member identity, provider identity, requested service, diagnosis, and supporting information can be mapped to the required FHIR/PAS structures according to the implementation guide and enterprise policy.

The mapping service should perform schema validation before transmission and retain both canonical and destination-specific representations. This allows a future PAS version or payer-specific contract to change without retraining the document model. It also makes failures attributable: extraction errors belong to the document layer, terminology errors to normalization/validation, and profile-conformance errors to the interoperability layer.

CMS requirements for impacted payers increase the practical importance of this separation because electronic prior-authorization APIs are expected to communicate

documentation requirements and request/response status [16]. IDP can complement such APIs by converting legacy or attachment-heavy inputs into structured, validated data, but it should not bypass the semantics or governance of the standardized exchange.

9. Security, Privacy, and Auditability

Prior-authorization documents may contain ePHI and other sensitive information. The HIPAA Security Rule establishes requirements for administrative, physical, and technical safeguards, including access control, audit controls, integrity, authentication, and transmission security [20]. An IDP platform should therefore encrypt documents and derived data at rest and in transit, enforce least-privilege access, maintain security-relevant audit logs, and isolate production data from development and model-training environments unless a governed de-identification or authorization process exists.

Data minimization is particularly important in AI pipelines because intermediate artifacts can multiply copies of sensitive information. Token caches, OCR text, model prompts, embeddings, reviewer screenshots, and debug logs should each have an explicit purpose and retention policy. General-purpose application logs should store identifiers and error codes rather than unrestricted document text. Where external model services are used, data-processing agreements, retention behavior, geographic constraints, and training-use policies must be reviewed before protected data are transmitted.

Auditability must cover both AI and non-AI decisions. For every automated downstream action, the platform should be able to reconstruct the source document, extracted evidence, model version, normalized value, validation responses, policy version, user or service identity, and final action. This evidence supports investigation, appeals, quality review, and controlled model updates.

10. Implementation Considerations

10.1. Service Boundaries and Technology Choices

A practical implementation can use independently deployable services for ingestion, classification, OCR/VDU, extraction, normalization, validation, policy routing, and orchestration. The architecture does not require microservices for every function; service boundaries should follow change rate, scaling behavior, security boundaries, and ownership. GPU-bound inference, for example, often scales differently from rules-based validation and API orchestration.

Enterprise Java, Python, or other platforms can host these components, but runtime behavior must be monitored. Production engineering concerns such as memory leaks, dependency conflicts, thread management, and performance degradation remain relevant to AI-enabled systems [1]. Model-serving containers should therefore expose health checks, bounded queues, timeouts, circuit breakers, and resource limits.

10.2. Model Selection and Versioning

No single model family should be assumed optimal for every document type. OCR plus LayoutLM-family extraction may be advantageous when token-level provenance is important [5]-[7]. OCR-free generative models may simplify some pipelines [9]. FormNet or BROS-like structural encoders may be useful for forms [11], [12], and language-independent layout representations may be relevant to multilingual documents [13]. Selection should be based on measured task performance, calibration, runtime cost, data-governance constraints, and ease of audit.

Every production inference result should record model identifier, model artifact hash or immutable version, preprocessing version, and configuration. Model upgrades should be evaluated on a frozen regression set that includes previously observed failure cases. Shadow evaluation is preferable before changing routing behavior for high-impact fields.

10.3. Human-in-the-Loop Operations

Review interfaces should minimize cognitive load by presenting the source region next to the extracted candidate and the precise reason for escalation. Reviewers should not need to infer whether the system is uncertain because of low OCR confidence, a member mismatch, conflicting documents, or a technical outage. Distinct reason codes support faster resolution and more reliable feedback data.

Reviewer actions should be captured as structured labels: confirm, correct, reject, request-more-information, or override-with-reason. These labels can later support supervised improvement, but retraining should use curated datasets rather than automatically learning from every operational edit. This avoids amplifying systematic reviewer shortcuts or transient business policies.

11. Discussion

The architecture addresses a recurrent gap between Document AI research and enterprise automation. Research benchmarks typically stop after classification, extraction, question answering, or structured generation. Enterprise workflows begin at that boundary. A payer or provider system must determine whether extracted data correspond to the correct member and provider, whether codes are allowed, whether required documentation is present, whether fields conflict, and whether the receiving system is available. By modeling these checks explicitly, the proposed design avoids treating a model confidence score as a business authorization signal.

The framework is also compatible with the continuing evolution of document models. If a future model materially improves extraction, only the inference component and its calibration may need replacement; validation contracts and downstream safety invariants remain stable. This reduces coupling and some forms of hidden technical debt described in production ML literature [22], [23]. Assurance similarly becomes compositional: model evidence, validation

evidence, policy evidence, and orchestration evidence can be tested separately and then combined [24].

The inclusion of the user-supplied software-defect-prediction studies [2], [3] is methodologically relevant rather than domain-equivalent. Those studies reinforce the need to compare models across multiple error-sensitive metrics. In IDP, a single accuracy number can obscure the difference between harmless formatting mistakes and unsafe auto-commit errors. Likewise, the inclusion of EmoVision [4] illustrates an application-level pattern in which perceptual AI is embedded within a broader interaction system; the present work extends that idea toward validated enterprise transaction processing.

The architecture does not imply that maximum straight-through automation is always the correct objective. In high-impact workflows, a lower automation rate with very low false auto-accept may be preferable to a higher automation rate with poorly characterized errors. Operational optimization should therefore be constrained by explicit safety bounds, not driven only by throughput or labor reduction.

12. Limitations and Threats to Validity

The principal limitation is the absence of a proprietary, labeled insurance or prior-authorization dataset and measured production telemetry. This paper therefore does not claim new OCR accuracy, extraction F1, latency reduction, cost savings, denial reduction, or staff-time improvement. Any such number would be unsupported. The evaluation is architectural and methodological, consisting of standards traceability, formal invariants, scenario analysis, and a specified empirical protocol.

Second, prior-authorization rules vary across payers, lines of business, jurisdictions, and clinical services. The validation taxonomy is general, but concrete rule logic must be derived from the applicable policy and maintained as those policies change. Third, FHIR/PAS integration does not eliminate legacy channels; organizations may need to support portals, X12-related workflows, attachments, and payer-specific interfaces concurrently. Fourth, human-review quality is itself a source of uncertainty and should be measured through inter-reviewer agreement and correction audits when the system is evaluated empirically.

Finally, privacy, fairness, and model drift require ongoing governance. Document quality may correlate with source organization, geography, device, or workflow, potentially creating uneven automation rates. Monitoring should therefore compare error and review rates across operationally meaningful cohorts where such analysis is lawful and appropriate. NIST AI RMF provides a general framework for continuous risk management [21], but organization-specific governance remains necessary.

13. Conclusion

This paper presented an AI-driven intelligent document-processing framework for insurance and prior authorization that extends beyond OCR and entity extraction. The central design principle is the separation of perceptual confidence from operational validity. Documents are classified and interpreted using OCR or visual-document-understanding models; extracted values are normalized; syntactic, semantic, contextual, and enterprise-reference validation is applied; and a risk-aware routing policy determines whether information can be automatically committed, requires further validation, must be reviewed, or should be rejected/requested again.

The architecture aligns document intelligence with enterprise realities: FHIR/PAS interoperability, ePHI security, auditability, idempotent downstream processing, dependency failures, model lifecycle governance, and human exception handling. Formal invariants define no-invalidated-commit, provenance completeness, idempotent side effects, and uncertainty containment. A reproducible evaluation protocol specifies the metrics necessary to test the system without inventing results. Future work should execute that protocol on a de-identified prior-authorization corpus, compare OCR-based and OCR-free baselines, calibrate risk-sensitive routing thresholds, and quantify the tradeoff between straight-through processing and false auto-accept under production-like conditions.

References

1. S. S. G. Bandari, “Mitigating Critical Challenges in Java Production Environments: Memory Leaks, Dependency Conflicts, and Performance Optimization in Enterprise Systems,” International Journal of Scientific Research in Computer Science, Engineering and Information Technology, vol. 10, no. 6, pp. 2492–2499, 2024, doi: 10.32628/CSEIT2425481.
2. S. K. Gunda, “Analyzing Machine Learning Techniques for Software Defect Prediction: A Comprehensive Performance Comparison,” in 2024 Asian Conference on Intelligent Technologies (ACOIT), Kolar, India, 2024, pp. 1–5, doi: 10.1109/ACOIT62457.2024.10939610.
3. S. K. Gunda, “Fault Prediction Unveiled: Analyzing the Effectiveness of Random Forest, Logistic Regression, and KNeighbors,” in 2024 2nd International Conference on Self Sustainable Artificial Intelligence Systems (ICSSAS), Erode, India, 2024, pp. 107–113, doi: 10.1109/ICSSAS64001.2024.10760620.
4. Krishna, G. V., Reddy, B. D., & Vrindaa, T. (2025). EmoVision: An Intelligent Deep Learning Framework for Emotion Understanding and Mental Wellness Assistance in Human Computer Interaction. International Journal of Artificial Intelligence, Data Science, and Machine Learning, 6(4), 14-20. https://doi.org/10.63282/3050-9262.IJAIDSML-V6I4P103
5. Y. Xu, M. Li, L. Cui, S. Huang, F. Wei, and M. Zhou, “LayoutLM: Pre-training of Text and Layout for Document Image Understanding,” in Proc. 26th ACM SIGKDD Int. Conf. Knowledge Discovery & Data Mining, 2020, pp. 1192–1200, doi: 10.1145/3394486.3403172.

6. Y. Xu et al., "LayoutLMv2: Multi-modal Pre-training for Visually-rich Document Understanding," in Proc. 59th Annual Meeting of the Association for Computational Linguistics and 11th Int. Joint Conf. Natural Language Processing, 2021, pp. 2579–2591, doi: 10.18653/v1/2021.acl-long.201.
7. Y. Huang, T. Lv, L. Cui, Y. Lu, and F. Wei, "LayoutLMv3: Pre-training for Document AI with Unified Text and Image Masking," in Proc. 30th ACM Int. Conf. Multimedia, 2022, pp. 4083–4091, doi: 10.1145/3503161.3548112.
8. M. Li et al., "TrOCR: Transformer-Based Optical Character Recognition with Pre-trained Models," Proc. AAAI Conf. Artificial Intelligence, vol. 37, no. 11, pp. 13094–13102, 2023, doi: 10.1609/aaai.v37i11.26538.
9. G. Kim et al., "OCR-Free Document Understanding Transformer," in Computer Vision – ECCV 2022, 2022, doi: 10.1007/978-3-031-19815-1_29.
10. S. Appalaraju, B. Jasani, B. U. Kota, Y. Xie, and R. Manmatha, "DocFormer: End-to-End Transformer for Document Understanding," in Proc. IEEE/CVF Int. Conf. Computer Vision (ICCV), 2021, pp. 993–1003.
11. C.-Y. Lee et al., "FormNet: Structural Encoding beyond Sequential Modeling in Form Document Information Extraction," in Proc. 60th Annual Meeting of the Association for Computational Linguistics, 2022, pp. 3735–3754, doi: 10.18653/v1/2022.acl-long.260.
12. T. Hong, D. Kim, M. Ji, W. Hwang, D. Nam, and S. Park, "BROS: A Pre-trained Language Model Focusing on Text and Layout for Better Key Information Extraction from Documents," Proc. AAAI Conf. Artificial Intelligence, vol. 36, no. 10, pp. 10767–10775, 2022, doi: 10.1609/aaai.v36i10.21322.
13. J. Wang, L. Jin, and K. Ding, "LiLT: A Simple yet Effective Language-Independent Layout Transformer for Structured Document Understanding," in Proc. 60th Annual Meeting of the Association for Computational Linguistics, 2022, pp. 7747–7757, doi: 10.18653/v1/2022.acl-long.534.
14. Z. Tang et al., "Unifying Vision, Text, and Layout for Universal Document Processing," in Proc. IEEE/CVF Conf. Computer Vision and Pattern Recognition (CVPR), 2023, pp. 19254–19264, doi: 10.1109/CVPR52729.2023.01845.
15. G. Jaume, H. K. Ekenel, and J.-P. Thiran, "FUNSD: A Dataset for Form Understanding in Noisy Scanned Documents," in 2019 Int. Conf. Document Analysis and Recognition Workshops (ICDARW), 2019, pp. 1–6, doi: 10.1109/ICDARW.2019.10029.
16. Centers for Medicare & Medicaid Services, "CMS Interoperability and Prior Authorization Final Rule (CMS-0057-F)," 2024. [Online]. Available: https://www.cms.gov/initiatives/burden-reduction/overview/interoperability/policies-regulations/cms-interoperability-prior-authorization-final-rule-cms-0057-f
17. Health Level Seven International, "FHIR Release 4 (v4.0.1)," 2019. [Online]. Available: https://hl7.org/fhir/R4/
18. Health Level Seven International, "Da Vinci Prior Authorization Support (PAS) FHIR Implementation Guide, v2.2.1," Mar. 2026. [Online]. Available: https://hl7.org/fhir/us/davinci-pas/
19. American Medical Association, "AMA survey indicates prior authorization wreaks havoc on patient care," 2024. [Online]. Available: https://www.ama-assn.org/press-center/ama-press-releases/ama-survey-indicates-prior-authorization-wreaks-havoc-patient-care
20. U.S. Department of Health and Human Services, "Summary of the HIPAA Security Rule," Office for Civil Rights. [Online]. Available: https://www.hhs.gov/hipaa/for-professionals/security/laws-regulations/index.html
21. National Institute of Standards and Technology, Artificial Intelligence Risk Management Framework (AI RMF 1.0), NIST AI 100-1, Jan. 2023.
22. D. Sculley et al., "Hidden Technical Debt in Machine Learning Systems," in Advances in Neural Information Processing Systems 28, 2015, pp. 2503–2511.
23. S. Amershi et al., "Software Engineering for Machine Learning: A Case Study," in 2019 IEEE/ACM 41st Int. Conf. Software Engineering: Software Engineering in Practice (ICSE-SEIP), 2019, doi: 10.1109/ICSE-SEIP.2019.00042.
24. R. Ashmore, R. Calinescu, and C. Paterson, "Assuring the Machine Learning Lifecycle: Desiderata, Methods, and Challenges," ACM Computing Surveys, vol. 54, no. 5, Art. No. 111, 2021, doi: 10.1145/3453444.
25. Gudi, S. R. (2024). AI-Driven Fax-to-Digital Prescription Automation: A Cloud-Native Framework Using OCR, Machine Learning, and Microservices for Pharmacy Operations. International Journal of Emerging Research in Engineering and Technology, 5(1), 111-116. https://doi.org/10.63282/3050-922X.IJERET-V5I1P113